



## Vehicle description for: TGS 40.480 6x4 BB SA



Illustration can deviate

### Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 40.480 6x4 BB SA
Vehicle type	Vehicle type Semitrailer tractor (SA)
Cab	TN cab: the flexible one (narrow, long, normal height)
Main wheel distance	3900 mm
Overhang	700 mm
Steering configuration	Left

### Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	40,000 kg	40,000 kg	40,000 kg
Front axle	9,000 kg	9,000 kg	9,000 kg
Rear axle	16,000 kg	16,000 kg	16,000 kg
Rear axle 2	16,000 kg	16,000 kg	16,000 kg

### Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	40,500 kg	70,000 kg	90,000 kg

7aed20c0d6-b282-4db4-9e32-d887e7b7d704



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.  
For further product information on the tire selection "selectively", please contact our sales staff.

## Vehicle characteristics

### Basic characteristics

<input type="checkbox"/>	Semitrailer tractor	0P2UA
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Destination: Yemen (YE)	0P3GU
<input type="checkbox"/>	Merchant tonnage 40 t	0P8LM
<input type="checkbox"/>	Basic layout of vehicle, especially for heavy-duty use and heavy payloads	0PGCW
<input type="checkbox"/>	Frame type, high	0P2TP
<input type="checkbox"/>	Vehicle type Semitrailer tractor (SA)	0P2UR
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in Arabic	0P2L0
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Signage in Arabic, additional	0P2JF
<input type="checkbox"/>	Cab position 640 mm (distance from frame lower edge to cab floor)	0PHBE

### Registration

<input type="checkbox"/>	Vehicle approval, N3G class	0P3JS
<input type="checkbox"/>	Maximum speed limiter, 100 km/h, electronic, engine speed regulation	0P2UD
<input type="checkbox"/>	Maximum vehicle noise level, 82 dB in acc. with UN/ECE-R 51.02	0PIND
<input type="checkbox"/>	Maximum vehicle width of 2,500 mm checked with respect to relevant cab components	0PIOH
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

### Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

### Application scope / transport tasks

<input type="checkbox"/>	Vehicle version municipal/public service deployment	0P0H7
<input type="checkbox"/>	Long-haul transport, special	0P6WG
<input type="checkbox"/>	042 SZM Heavy-duty transport	0P2QN
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0
<input type="checkbox"/>	Vehicle preservation for overseas transport	0P2UY

### Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

### Horizontal and vertical loads

<input type="checkbox"/>	40,000 kg permitted gross load, vertical, nat. appr.	0P5RB
<input type="checkbox"/>	40,000 kg permitted gross load, vertical, tech.	0P5UW
<input type="checkbox"/>	40,000 kg permitted gross load, vertical, tech. Plus	0P8IL

### Notification texts

<input type="checkbox"/>	Notice: Reduced front overhang angle due to long radiator	0PHPG
--------------------------	-----------------------------------------------------------	-------



- Without note (propshaft wear) 0PJRV

## Chassis

---

### Vehicle frame (wheelbase, overhang, ...)

---

- Main wheelbase, 3,900 mm 0P2ZK
- Wheelbase between rear axles, 1,400 mm 0P3BX
- Frame overhang, rear, 700 mm 0P3EQ
- Main frame side member thickness, 9.5 mm 0P0Y7
- Vehicle rear, angled end of frame 0P0XS
- Semitrailer auxiliary frame 0P0XV

### Exhaust system, air intake

---

- Exhaust silencer, side, left 0P1BG
- Exhaust tailpipe, towards rear 0P1BQ
- Air intake, behind cab, raised 0P0AY
- Pre-separator for engine air intake 0P0BA

### Battery cases, batteries, alternator

---

- Battery, 12 V, 175 Ah, 2 units, maintenance free 0P0WA
- Alternator, Basic 0P1BV
- Medium battery box, 2 batteries 0P0WU
- Battery box, left 0P0WO
- Main battery switch, electric 0P0WE
- Safety cut-out 0P1V2
- Lockable battery box, with padlock 0P0WL

### Tanks and fuel line

---

- Fuel tank capacity 590 l, right 0P4EL
- Fuel tank, right, aluminium 0P4GM
- Tank cross-section, right, medium 0P4HE
- Fuel tank cap, lockable for master key system 0P4H5
- Fuel pre-filter position on the battery box 0PIW9

### Frame attachments

---

- Without underride protection, front 0P1FM
- Working platform, with step 0P0VE
- Without underride protection, side 0P1FG
- Spare wheel, provisionally mounted 0P1GR
- Final cross member, with hole pattern 160 x 100 mm 0P1SB
- Without underride protection, rear 0P1FB
- Without body attachment brackets/thrust plates 0P0X6

### Pneumatic brakes, compressed-air generation, brake system

---

- Air compressor, 2-cylinder, 720 ccm 0P0AI
- Compressed-air treatment, pneumatically controlled 0P0AB
- Steel compressed-air tank 0P0XH
- Electronic brake system (EBS) 0P0BL
- Anti-lock braking system (ABS), Offroad, with additional off-road logic 0P0BF



<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/>	Drum brakes on front axle	0P11A
<input type="checkbox"/>	Drum brakes on rear axle	0P115
<input type="checkbox"/>	Drum brakes on 2nd rear axle	0P11F
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Brake cylinder with parking brake for increased gross weight	0P8QF
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	Anti-jackknifing brake, manual, can be operated next to driver's seat	0P0CJ
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF

#### Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Emergency braking signal, hazard light activation, automatic	0P0CG
<input type="checkbox"/>	Acoust. Reversing warning system deactivatable when reverse gear selected	0P3CE
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	Side marker lights, LED	0P2BJ

#### Driveline/running gear

##### Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D2676 LF03, 353 kW (480 hp) output, 2,300 Nm torque, Euro 2	0P6BO
<input type="checkbox"/>	Fuel filter, for fuels up to Cleanliness Class 21	0PHIH
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap	0P0AT
<input type="checkbox"/>	Engine dry-air filter, with safety insert	0P0B8
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Anti-noise skirt, engine	0P2E7
<input type="checkbox"/>	Engine radiator Visco fan, high cooling output	0P0H0
<input type="checkbox"/>	Fan control for start of cooling with low coolant temperature (e.g. hot country)	0P0K5
<input type="checkbox"/>	Reduction of dust swirl through radiator fan	0P1YE
<input type="checkbox"/>	Engine cooler, extended	0P4XY
<input type="checkbox"/>	Radiator protection, lower	0P1XE
<input type="checkbox"/>	Front radiator protection, grille	0P1VP
<input type="checkbox"/>	Engine oil dipstick and digital oil level gauge	0P0B6
<input type="checkbox"/>	Warning message for engine coolant level, with advance warning	0P0KA
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK
<input type="checkbox"/>	Service product level indicator and intake system vacuum	0P3KT

##### Gearbox, clutch

<input type="checkbox"/>	MAN TipMatic 12.28 OD	0P5VW
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	MAN TipMatic Offroad gearbox shift strategy, up to 70,000 kg	0P0F4
<input type="checkbox"/>	Expansion, MAN TipMatic Heavy-duty transport driving program, up to 90,000 kg	0P0FG
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry	0P0DT



- Driveline propshaft, reinforced 0P0E2
- Propshaft, 2nd rear axle, reinforced 0PGCF
- Gearbox heat exchanger 0P0FW

## Wheels, tyres

- Required tyre speed index K 0PFW3
- Tyres, front axle, Bridgestone 325/95R24 G584 special TT 0PJH4



- Rim type, front axle, steel, split 0P0OZ
- Rim size, front axle, 10-hole, 8.5-24 0P0NG
- Wheel nut cover ring, front axle 0P0PR
- Tyres, rear axle, Bridgestone 325/95R24 G584 Special TT 0PJEO



- Rim type, rear axle, steel, split 0P0ON
- Rim size, rear axle, 10-hole, 8.5-24 0P0MS

7ad20c0e-b282-4db4-9e32-d887e7b7d7c4



- Tyres, 2nd rear axle, Bridgestone 325/95R24 G584 Special TT

0PJFJ



- |                                                                      |       |
|----------------------------------------------------------------------|-------|
| □ Rim type, 2nd rear axle, steel, split                              | 0P0P9 |
| □ Rim size, 2nd rear axle, 10-hole, 8.5-24                           | 0P0O5 |
| □ Spare wheel, in accordance with configuration for front axle tyres | 0P0MH |
| □ Tyre inflation hose, 20 m, with pressure gauge                     | 0P1UA |
| □ Centring sleeves for rim mounting                                  | 0PHZW |

## Axles

- |                                                                                                     |       |
|-----------------------------------------------------------------------------------------------------|-------|
| □ 6x4                                                                                               | 0P3B9 |
| □ Steering ratio, indirect                                                                          | 0P1JY |
| □ Steering oil tank with electrical measuring sensor                                                | 0P1JV |
| □ Front axle, 9,200 kg, not driven, straight, steered, not liftable                                 | 0P5EX |
| □ Mudguard, front axle                                                                              | 0P1AT |
| □ Rear axle, 16,000 kg, planetary axle with drive shaft, straight, not steered, not liftable        | 0P4ZQ |
| □ Mudguard, rear axle, plastic half shells in front of rear axle                                    | 0P1AO |
| □ 2nd rear axle, 16,000 kg, planetary axle without drive shaft, straight, not steered, not liftable | 0P4Y9 |
| □ Mudguard, plastic half shells, behind 2nd rear axle, with transfer tarpaulin over both rear axles | 0P1AY |
| □ Splash guard mat on mudguard, 2nd rear axle                                                       | 0P1XY |
| □ Axle ratio, $i = 5.33$                                                                            | 0P0DD |
| □ Differential locks on driven rear axles                                                           | 0P0DI |
| □ Without differential locks, front axles                                                           | 0P0DL |

## Axle control system and suspension

- |                                                                     |       |
|---------------------------------------------------------------------|-------|
| □ Leaf-spring suspension on front axle, parabolic, 3-leaf, steel    | 0P1JE |
| □ Leaf-spring suspension on rear axle, parabolic, 6-leaf, steel     | 0P1J3 |
| □ Leaf-spring suspension on 2nd rear axle, parabolic, 6-leaf, steel | 0P1JM |
| □ Spring load-bearing capacity front axle 9,500 kg                  | 0P5C4 |
| □ Spring load-bearing capacity of rear axle, 20,000 kg              | 0P5BX |
| □ Spring load-bearing capacity of 2nd rear axle, 20,000 kg          | 0P5C9 |
| □ Shock absorbers on front axle, reinforced                         | 0P1M6 |
| □ Shock absorbers on rear axle                                      | 0P1LQ |
| □ Shock absorbers on 2nd rear axle                                  | 0P1M9 |
| □ Stabiliser, front axle                                            | 0P1LD |



<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, 2nd rear axle	0P1LH
<input type="checkbox"/>	Wishbone, reinforced	0P6ZS
<input type="checkbox"/>	Without trailer air suspension control	0PHN2

## Cab

---

### Cab and cab exterior

---

<input type="checkbox"/>	TN cab: the flexible one (narrow, long, normal height)	0P2DF
<input type="checkbox"/>	Cab mount, Basic	0P1V8
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	Roof spoiler, 600 mm adjustment range	0P1X7
<input type="checkbox"/>	Roof spoiler adjustment upon delivery, transport position	0P1XA
<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, hinged	0P1V0
<input type="checkbox"/>	Central locking, with remote control	0P1WR
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	Door extension, driver's and co-driver's side	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, with window incl. protective guard	0P1VC

### Lights and acoustic signals on cab exterior (headlights, horn, ...)

---

<input type="checkbox"/>	Without light and headlight package	0PKWU
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Daytime driving lights, H7	0P2BN
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Cornering light, H7	0P1YF
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Turn signal lights, sides, LED	0P1Z7
<input type="checkbox"/>	Compressed-air horn, 2 units, cab roof	0P1UW
<input type="checkbox"/>	Revolving beacons, halogen, yellow, with function monitoring	0P2B9
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Spotlight, rear of cab, lower, outside	0P1Z2
<input type="checkbox"/>	Spotlight, LED, white	0PJQA
<input type="checkbox"/>	Switch for spotlight/manoeuvring light	0P5U5
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

### Mirrors and mirror replacements

---



<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable with manoeuvring aid	0P2CB
<input type="checkbox"/>	Mirror housing, painted, cab colour	0P2CN
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Without mirror package	0PKWV

## Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Driver's seat arm rests	0P2OE
<input type="checkbox"/>	Adjustment of seat belt height, driver's seat	0P4XQ
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6
<input type="checkbox"/>	Indicator, seat belt, 1st row of seats, acoustic and visual	0P8L1
<input type="checkbox"/>	Without driver's seat package	0PKXV
<input type="checkbox"/>	Without co-driver's seat package	0PKXU

## Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Instrumentation, Basic km/h	0P3L3
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Socket, cab centre, 2 units, 12 V and 24 V	0P2HX
<input type="checkbox"/>	2 pull-out cup holders in instrument panel	0P2FA
<input type="checkbox"/>	Plug-in ashtray, instrument panel in middle section, 1 unit	0P2FO
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Preparation for radio with CB radio antenna on cab roof	0P2NK
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/>	Without storage tray next to seat	0PJRS

## Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

## Bunk area

<input type="checkbox"/>	1 bunk, 90 mm mattress, with stowage facilities, sockets	0PKMW
<input type="checkbox"/>	Bunk, bottom, with slatted support	0P2GX
<input type="checkbox"/>	Fabric cover for bottom bunk	0P2I5
<input type="checkbox"/>	Standard bed mattress, bottom, 90 mm	0P2GM
<input type="checkbox"/>	Cross-cab curtain, rear seats	0P2GP
<input type="checkbox"/>	Storage box, rear left, accessible from outside with flap and from inside below suspended tray	0P2H0
<input type="checkbox"/>	Storage box, rear, right, accessible from outside with flap and from inside below suspended tray	0P2H4

## Cab interior

<input type="checkbox"/>	Colour scheme for interior styling, dark	0P2I6
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT



<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Roller blind for door windows, internal, mechanical, driver's side	0P2FH
<input type="checkbox"/>	All-round curtain	0P2GS
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 1 unit, driver's side	0P2IQ
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Carpet, on engine tunnel	0P2I9
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	Refrigerator, permanently installed and storage space, to rear of centre area	0P2HE
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2
<input type="checkbox"/>	Entry handles, standard	0PHPK
<input type="checkbox"/>	Without driver's workplace package, Comfort	0PKXT
<input type="checkbox"/>	Interior light, reading light (driver's side)	0PKMY
<input type="checkbox"/>	Without stowage and storage space package	0PKXS

## Accessories and tools

<input type="checkbox"/>	Fire extinguisher, 2 kg, 1 ea., rear area of cab, inside, in vehicle documentation language	0P2YE
<input type="checkbox"/>	Compressed-air connection, cab, with compressed-air hose and gun	0P2FM
<input type="checkbox"/>	Jack, 25,000 kg	0P3F9
<input type="checkbox"/>	Without accessories and tools package	0PKXA
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	First aid kit	0P3F3
<input type="checkbox"/>	Warning triangle, 1 units	0P3FI
<input type="checkbox"/>	Operator's manual in Arabic, printed, additional	0PHZY

## Intelligent Truck

### Assistance systems

<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5
<input type="checkbox"/>	Without driving fitness detection system	0PHN5
<input type="checkbox"/>	Without Front Detection	0PHNA
<input type="checkbox"/>	Without traffic sign recognition	0PHNE
<input type="checkbox"/>	Without Reversing Motion System	0PHNV
<input type="checkbox"/>	Without distance warning system	0PKA0

### Infotainment (radio,...)

<input type="checkbox"/>	Radio preparation, 12 V	0P2M4
<input type="checkbox"/>	Loudspeaker, door, 2 units, 1 left and 1 right	0P2ME
<input type="checkbox"/>	No navigation map	0P2N2

## Bodies/interfaces

### Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	2-line semitrailer brake connection, behind cab, spiral cable with standard coupling	0P1O2
--------------------------	--------------------------------------------------------------------------------------	-------



<input type="checkbox"/>	Trailer socket behind cab, 24 V, 15-pin	0P1P9
<input type="checkbox"/>	Spiral cable to semitrailer, electr., one unit, for trailer socket behind cab, 24-V, 15-pin to 15-pin	0P8NY
<input type="checkbox"/>	Spiral cable to semitrailer, electric, for trailer socket ABS, behind cab	0P8O1
<input type="checkbox"/>	Fifth-wheel pick-up plate installation height, 40 mm (up to max. 36,000 kg fifth-wheel coupling load)	0P6ZZ
<input type="checkbox"/>	JOST JSK 38 C 3.5" fifth-wheel coupling	0P1RP
<input type="checkbox"/>	Kingpin, 3.5" diameter	0P1RZ
<input type="checkbox"/>	Manufacturer of fifth-wheel coupling: Jost	0PBY1
<input type="checkbox"/>	Fifth-wheel coupling installation height, 190 mm	0P1PT
<input type="checkbox"/>	Fifth-wheel coupling, manual lubrication	0P6XR
<input type="checkbox"/>	Rubber joint bearing, fifth-wheel coupling	0PBY6
<input type="checkbox"/>	Fifth-wheel coupling actuation, normal handle	0P1Q1
<input type="checkbox"/>	Without sensing of the fifth-wheel coupling	0PHN7
<input type="checkbox"/>	Fifth-wheel lead, 1,125 mm	0P5AY

#### Interfaces to trailer (e.g. trailer coupling, brake connections...)

<input type="checkbox"/>	Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Trailer socket for anti-lock braking system (ABS), behind cab	0P1O5

#### Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab	0P2NA
<input type="checkbox"/>	Interface for vehicle data (FMS)	0P2J3

#### PTOs

<input type="checkbox"/>	PTO, gearbox-dependent, type NH/4c, without flange, f=1.14, position approx. 3:30 o'clock	0P6XM
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0

#### Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
--------------------------	------------------------------------------------------------------------------	-------

### Paintworks

#### Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
<input type="checkbox"/>	Top coating, roof spoiler	0P6X3

#### Paintwork, cab, bottom

<input type="checkbox"/>	Top coating, door extension and step units	0P6X8
<input type="checkbox"/>	Top coating, mudguard, behind cab	0P6YF
<input type="checkbox"/>	Top coating, bumper, steel	0P6YO

#### Paintwork, chassis

<input type="checkbox"/>	Top coating, chassis	0P6YC
--------------------------	----------------------	-------



- Top coating, rims, steel, white-aluminium 0P6YL

### Additional operating equipment

- Vehicle plate must reflect GTW 90,000 AS technical+ ZW001

### Colour

<input type="checkbox"/>	Top coating, door extension and step units	PURE WHITE RAL 9010	N
<input type="checkbox"/>	Top coating, mudguard, behind cab	PURE WHITE RAL 9010	N
<input type="checkbox"/>	Top coating, bumper, steel	PURE WHITE RAL 9010	N
<input type="checkbox"/>	Top coating, cab	PURE WHITE RAL 9010	A
<input type="checkbox"/>	Top coating, roof spoiler	PURE WHITE RAL 9010	N
<input type="checkbox"/>	Top coating, chassis	GRAPHITE BLACK RAL 9011	N

7ad20c0d6-b282-4db4-9e32-d887e7b7d704



## Technical data: TGS 40.480 6x4 BB SA / L34JAA02

Vehicle type: Vehicle type Semitrailer tractor (SA)  
 Cab: TN cab: the flexible one (narrow, long, normal height)  
 Drive Type: 6x4

TD018	Statutorily permissible gross vehicle weight	40000
TD025	Technically permissible gross vehicle weight	40000
TD031	Statutorily permissible gross train weight	40500
TD032	Statutorily permissible trailer load	0

<b>Lengths</b>		<b>mm</b>
TD071	Total length	7717.0
TD063	Front vehicle overhang	1607.0
TD057	Wheelbase between front axles	0
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	675.0
TD072	Distance from first front axle to body	865.0
TD067	Distance to kingpin from front axle, nominal position	4175.0
TD074	Slew radius, front	3210.0
TD075	Slew radius, rear	2212.0
TD068	Coupling length	7549.0

<b>Widths</b>		<b>mm</b>
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

<b>Frame</b>		<b>mm</b>
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

<b>Heights</b>		<b>mm</b>
TD033	Maximum external height, unladen	3983.0
TD082	Total transport height, unladen	3559.0
TD034	Maximum external height, laden	3885.0
TD035	Frame height at theoretical rear wheelbase, unladen	1259.0
TD036	Frame height at theoretical rear wheelbase, laden	1186.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	1573.0
TD052	Height of fifth-wheel coupling above ground, laden	1500.0

<b>Circle dimensions</b>		<b>m</b>
TD055	Track circle diameter	18.0
TD056	Wall-to-wall turning circle diameter	19.7

<b>Weights/loads</b>		<b>kg</b>
TD026	Chassis weight with cab	10751.0
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---
TD029	Payload	---

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.